

Silkolene[®]

SILKOLENE SUPER 4 RANGE

Semi-synthetic 4-stroke engine oil for modern motorcycles

Description

SILKOLENE SUPER 4 grades are semi synthetic 4-stroke engine oils designed for use in both On-Road and Off-Road motorcycles. They protect the engine and transmission with advanced additive chemistry from start-up to full power. SILKOLENE SUPER 4 grades are blended with a high performance additive system incorporating detergents, dispersants and load carrying agents to give excellent engine cleanliness and minimum component wear. SILKOLENE SUPER 4 uses a balanced formulation to ensure correct operation of oil immersed clutches and other drive line components.

Application

SILKOLENE SUPER 4 10W-30, 10W-40 and 20W-50 are multigrade 4-Stroke engine oils specifically designed for 4-stroke motorcycle engines On or Off-Road.

Advantages

- A choice of two viscosity grades
- Suitable for use in all 4-stroke motorcycle engines on or off road
- Anti-wear and load carrying agents protect camshafts and bearings and other internal components
- Advanced inhibitors and high quality base fluid minimise internal sludge and varnish deposits
- Balanced frictional characteristics give precise and slip-free clutch operation
- Extreme pressure and lubricity additives ensure quiet and trouble-free gearbox lubrication

Specifications / Approvals

- JASO MA2
- API SL Performance



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products

Silkolene Product Information



Typical Data: SILKOLENE SUPER 4 RANGE

SILKOLENE SUPER 4			10W-30	10W-40	20W-50
Characteristics	Test Method	Unit			
SAE Rating			10W-30	10W-40	20W-50
Specific gravity	IP160		0.860	0.862	0.875
Kinematic Viscosity @ 40°C	IP71	mm ² /s	67.3	91.7	150.0
Kinematic Viscosity @ 100°C	IP71	mm ² /s	10.7	14.0	18.7
Viscosity Index (VI)	IP226		149	157	140
Cold Crank Viscosity @ -25 °C	ASTM D5293	cP	3987	4700	
Cold Crank Viscosity @ -15 °C	ASTM D5293	cP			6700
Pour point	IP15	°C	-42	-36	-28
Flash Point (Closed Cup)	IP34	°C	200	210	220

Reviewed 01/08/2019



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products